Publication number:

0 308 274 A2

@

ادر (

# EUROPEAN PATENT APPLICATION

② Application number: 88308663.9

9 Int. Cl.4: G 03 C 1/68

2 Date of filling: 19.09.88

@ Prionty: 18.09.87 US 98358

Oate of publication of application: 22.03.89 Builetin 89/12

Designated Contracting States: DE FR GB

Applicant: THE MEAD CORPORATION 2000 Courthouse Plaza NE.
Dayton Ohio 45401-1817 (US)

inventor: Gottschalk, Peter 71 Gershwin Drive Centerville Ohio 45459 (US)

> Schuster, Gary B. 1911 Augusta Drive Champaign Illinois 61821 (US)

Neckers, Douglas C. 108 Secor Woods Perrysburg Ohio (US)

Representative: Deans, Michael John Percy et al Lloyd Wise, Tregear & CO. Norman House 105-109 Strand London WC2R OAE (GB)

Photoherdenable compositions and processes for coating a substrate.

A substrate is coated with a visible light sensitive composition comprising a free radical addition polymenzable or cross linkable material and a photobleachable ionic dye-counter ion compound capable of absorbing visible light and generating free radicals. The composition is exposed to light to harden the composition, and to bleach the composition to an essentially colouriess state. Also described are photohardenable compositions containing photobleachable ionic dye-counter ion compounds as photoinitiators useful in the aforesaid process.

#### Description

# PHOTOHARDENABLE COMPOSITIONS AND PROCESSES FOR COATING A SUBSTRATE

This invention relates, in one aspect, to photohardenable compositions, and in another aspect, to processes for coating a substrate. European Patent Specification EP-A-0223587 relates to photocurable compositions containing ionic dye complexes as photoinitiators. These complexes directly or indirectly yield free radicals upon exposure to actinic radiation and particularly visible light.

By nature, compositions which are sensitive to visible light appear coloured to the human eye. There are applications in which it would be desirable to use compositions which can be cured upon exposure to visible light were it not for the coloured appearance of these compositions. For example, in laminating glass, if the composition is coloured it imparts a tint to the glass which is generally undesirable. Similarly, a visible initiator would be advantageous in coating optical fibres were it not for its coloured appearance.

We have now appreciated that in such applications, photobleachable ionic dye complexes would be particularly useful. We have observed that some of the dyes disclosed in the aforementioned EP-A-0223587 are photobleachable. The present invention may thus be seen at least in part as a selection from what is described in the said European Application.

The present invention broadly relates in one aspect to visible light sensitive photocurable compositions containing a photobleachable ionic dye complex as an initiator.

In accordance with this first aspect of the invention, there is provided a photohardenable composition comprising a free radical addition polymerizable or crosslinkable material, characterised in that it further comprises a photobleachable ionic dye-counter ion compound capable of absorbing visible light and of producing free radicals to initiate polymerization or crosslinking of said composition.

Another manifestation of the present invention is as a process for coating a substrate in which the coating composition contains a photobleachable ionic dye complex as a photoinitiator, and the coating is exposed to light to cure the composition and bleach the dye.

In accordance with this second and alternative aspect of the invention, we provide a process for coating a substrate characterised in comprising the steps of: coating said substrate with a visible light sensitive composition comprising a free radical addition polymerizable or crosslinkable material and a photobleachable ionic dye-counter ion compound capable of absorbing visible light and generating free radicals: exposing said composition to light to harden said composition; and bleaching said ionic dye to an essentially colourless state.

Our compositions and process are useful in applications in which an essentially colouriess (e.g. clear, transparent or white) radiation cured coating are desired. Typical examples of such applications are in laminating glass, coating optical fibres or in coating compositions containing white pigments such as litanium dioxide.

lonic dye complexes useful in the practice of the present invention are included within the general description of EP-A-0223587. Xanthene dye complexes useful in the practice of this invention are described in our U.S. Patent Application Serial No. 057544 filed 3rd June 1987.

The ionic dye complexes useful in the present invention are characterised in that they are photobleachable. The polymerizable or crosslinkable materials described in the aforementioned applications are useful herein. The photoinitiator systems described in the aforementioned applications are also useful herein with the requirement that the ionic dye-counter ion compounds be photobleachable. Of the dye complexes disclosed in EP-A-0223587, all of the cyanine dye complexes are photobleachable with varying efficiency and speed Some of the more efficient photobleachable complexes are:

45

25

30

50

55

60

740 nm Systems

5

:0

25

10

35

The azine dye complex of Methylene Blue and triphenylbutylborate is one of the most efficient complexes in terms of photobleachability. Its structure is

$$(CH_3)_2$$
 N  $(CH_3)_2$  658 nm  $Ph_3$   $B^{\Theta}_{N}$   $-C4$   $Hq$ 

Rose Bengal-onium dye complexes are also photobleachable. Of these, complexes of Rose Bengal and its benzylester with diphenyliodonium ions (including di(4-t-butylphenyl)iodonium ions) are photobleachable with high efficiency.

For the purpose of the present invention, the photobleachable dye complexes may bleach upon exposure to visible light upon curing the compositions, or they may be bleached upon post-exposure to a bleaching radiation such as ultraviolet radiation.

# Claims 50

- A photohardenable composition comprising a free radical addition polymerizable or crosslinkable material, characterised in that it further comprises a photobleachable ionic dye-counter ion compound capable of absorbing visible light and of producing free radicals to initiate polymerization or crosslinking of said composition.
- 2. A photohardenable composition according to Claim 1, further characterised in that, prior to exposure, said ionic dye-counter ion compound is a stable, non-transient compound.
- 3. A photohardenable composition according to Claims 1 or 2, further characterised in that said ionic dye-counter ion compound is soluble in said free radical addition polymerizable or crosslinkable
- 4. A photohardenable composition according to any preceding claim, further characterised in that, following exposure of said ionic dye-counter ion compound to light, an electron is transferred from said dye to said counter ion or from said counter ion to said dye, the rate of said electron transfer being greater.

### EP 0 308 274 A2

than a diffusion controlled rate.

5

:0

15

20

25

30

35

40

15

50

5.5

- A photohardenable composition according to any preceding claim, further characterised in that said compound is an anionic dye compound.
- A photonardenable composition according to Claim 5, further characterised said anionic dye is selected from xanthene and oxonol dyes.
- 7. A photohardenable composition according to Claims 5 or 6, further characterised in that said ionic dye counter ion compound is an anionic dye-onium ion complex or an anionic dye-pyryllium ion complex.
- 8. A photohardenable composition according to Claim 7, further characterised in that said ionic dye-counterion compound is a complex of Rose Bengal or Rose Bengal benzyl ester with diphyliodonium ions.
- 9. A photohardenable composition according to any of claims 1 to 4, further characterised in that said ionic dye counter ion compound is a cationic dye-boarate anion compound represented by the formula (I):

where D is a cationic dye moiety; and R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> and R<sup>4</sup> are the same or different and selected from alkyl, aralkyl, alkaryl, alkenyl, alkynyl, alicyclic, heterocyclic, and allyl groups.

- 10. A photohardenable composition according to Claim 9, further characterised in that said cationic dye is selected from cationic methine, polymethine, triarylmethane, indoline, azine, thiazine, xanthene, oxazine, acridine, cationic cyanine, carbocyanine, hemicyanine, rhodamine, and azamethine dyes.
- 11. A photohardenable composition according to Claim 10, further characterised in that at least one of R1, R2, R3 and R4 is an alkyl group.
- 12. A photohardenable composition according Claim 11, further characterised in that  $R^1, R^2$ , and  $R^3$  are aryl groups and  $R^4$  is an alkyl group.
- 13. A photohardenable composition according to Claim 10, further characterised in that said dye is Methylene Blue.
- 14. A photohardenable composition according to Claim 10, further characterised in that said cationic dye is selected from

65

60

15. A photohardenable composition according to any preceding claim, further characterised in that said polymerizable or crosslinkable material contains an ethoylenically unsaturated compound.

16. A process for coating a substrate characterised in comprising the steps of: coating said substrate with a visible light sensitive composition comprising a free radical addition polymerizable or crosslinkable material and a photobleachable ionic dye-counter ion compound capable of absorbing visible light and generating free radicals; exposing said composition to light to harden said composition; and bleaching said lonic dye to an essentially colourless state.

17. A process according to Claim 16, further characterised in that said bleaching step takes place in the course of said exposure to light step to harden the composition.

18. A process according to Claim 18, further characterised in that said bleaching step comprises exposure to a bleaching radiation such as ultra-violet radiation post exposure to said visible light.

60

55

40

45

**65** 

## AU 1507

(12) PATENT ABRIDGMENT (11) Document No. AU-B-12624/88 (19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 608573

. - . -..

164 Title
COREACTIVE PHOTOINITIATORS FOR PHOTOPOLYMERISATION OF
ETHYLENICALLY UNSATURATED MONOMERS

gernational Patent Classification(s)

51) C08F 002/50 C07C 049/84 C07C 059/70 C07C 083/10 C07C 093/06 C07C 109/08 C07C 117/00 C07C 161/C4 C27D 303/17 C07D 303/26 C07D 335/16 C07D 409/12 C07F 007/18 C09D 007/12 C07C 069/712 C07C 103/178 C07C 119/042

(21) Application No. : 12624/88

(22) Application Date: 02.02.88

(30) Priority Data

(31) Number (32) Date (33) Country 3707891 12.03.87 DE FEDERAL REPUBLIC OF GERMANY 3738567 13.11.87 DE FEDERAL REPUBLIC OF GERMANY

(43) Publication Date: 15.09.38

(44) Publication Date of Accepted Application: 11.04.91

(71) Applicant(s)
MERCK PATENT GESELLSCHAFT MIT BESCHRANKTER HAFTUNG

D. MANFRED KOHLER; Dr. JORG OHNGEMACH; Dr. EIKE POETSCH; Dr. RUDOLF EIDENSCHINK; Prof. Dr. GERHARD GREBER; Dr. DIETER DORSCH; Dr. JURGEN GEGLHAUS; Dr. KONRAD DORFNER; Dr. HANS-LUDWIG HIRSCH

(14) Attorney or Agent ETHUR'S CAVE & CO, GPO Box 3876, SYDNEY NSW 2001

Filor Art Documents AU 553151 87832/82 C08F 2/50 EP 337209

57) C'aim

Use of compounds of the formula i, RG-A-IN

in which

il is a photoinitiator basic structure



where  $R^2$ ,  $-cR^3R^4R^5$  or  $-r(R^6)_2$ 

 $g^{\frac{1}{2}}$  is H,  $C_{1-12}$ -alkyl, halogen or the RG-A- group, or two  $R^{\frac{1}{2}}$  radicals in the ortho position

(10) 608573

to the carbonyl group together are alternatively -S-,

 $R^2$  is H, halogen,  $C_{1-12}$ -alkyl or  $C_{1-12}$ -alkoxy or the RG-A- group,

 $R^3$ ,  $R^4$  in each case independently of one another are H,  $C_{1-12}$ -alkyl,  $C_{1-12}$ -alkenyl,  $C_{1-12}$ -alkoxy or phenyl, or together are  $C_{2-6}$ -alkylene,

R<sup>5</sup> is C<sub>1-6</sub>-alkyl, C<sub>1-6</sub>-alkanoyl, phenyl or benzoyl, each of which is optionally substituted by halogen, C<sub>1-6</sub>-alkyl or C<sub>1-6</sub>-alkoxy, R<sup>7</sup> is H, C<sub>1-6</sub>-alkyl or C<sub>1-6</sub>-alkanoyl, is a spacer group 2((CH<sub>2</sub>)<sub>0</sub>Y)<sub>n</sub>-((CH<sub>2</sub>)<sub>m</sub>X)<sub>1</sub>

X, Y and Z, in each case independently of one another, are a single bond -O-, -S-, -NH-, -CO-, -CONH-, -O-CO+, -NH-CO- or -NH-COO-.

l and m are the numbers i to 4, n and o are the numbers 0 to 4 is one of the functional reactive groups HO-, HS-, H2N-, halogen, HO-CO-, H2N-CO-, O=C=N-, S=C=N-, N3-, SO3H, SO2Cl; R<sup>C</sup>R<sup>D</sup>C=CR<sup>a</sup>- where R<sup>a</sup>, R<sup>D</sup> and R<sup>C</sup> are in each case H or CH3, and with the proviso that 2 is not -COO- when n is 0 and R<sup>S</sup> is OR<sup>7</sup>; RG is furthermore halogen, cyclopropyl, oxiranyl, O=C=N-R<sup>d</sup> where R<sup>d</sup> is C1-6-alkylene or phenylene, N<sup>2</sup>/<sub>2</sub> - (R<sup>e</sup>)3Si where R<sup>e</sup> is halogen, C1-12-alkyl, C1-12-alkoxy or C1-12-alkanoyloxy

as coreactive photoinitiators for photopolymerization of systems containing ethylenically unsafurated compounds.

2. Use of the compounds of the general formula I according to Claim 1 together with known photoinitiators and/or sensitizers.

(11) AU-B-12624/88

3

(10) 608573

Process for photopolymerization of systems containing ethylenically unsaturated compounds, characterized in that at least one compound of the formula I is added as a coreactive photoinitiator to the mixture to be polymerized before initiation of the photopolymerization.

The compounds of the formula I : : 4-[2-(oxiranylmethoxy)ethoxy]phenyl 2-hydroxy-2-propyl 4-(2-allyloxyethoxy)phenyl 2-hydroxy-2-propyl ketone 4-[2-(3-triethoxysilylpropoxy)ethoxy]phenyl 2-hydroxy-2procyl ketone 4-(2-azidoethoxy)phenyl 2-hydroxy-2-propyl ketone 4-thydroxycarbonylmethoxy)phenyl 2-hydroxy-2-propyl ketone 4-allyloxyphenyl 2-hydroxy-2-progyl ketone 4-oxiranylmethoxyphenyl 2-hydroxy-2-propyl ketone 4-[3-(triethoxysily()propoxy]pheny( 2-hydroxy-2-propy( ketone 4-22-(3-triethorysily(propylthio)ethy(]sheny( 2-hydroxy-2propyl ketone 4-(2-chloroethoxy)phenyl (2-hydroxy-2-propyl) ketone 4-(oxiranylmethoxycarbonylmethoxy)phenyl 2-hydroxy-2-propyl ketone 4-oxiranylmethoxyphenyl a-isopropoxybenzyl ketone 4-[3-(triethoxysilyl)propoxy]phenyl a-isopropoxybenzyl ketone 4-oxiranylmethoxyphenyl a, a-dimethoxybenzyl ketone 4-[3-(triethoxysilyl)propoxy]phenyl-a,a-dimethoxybenzylketone 4-(2-isocyanatoethoxy)phenyl 2-hydroxy-2-propyl ketone

4-(2-isothiocyanatoethoxy)phenyl 2-hydroxy-2-propyl ketone
4-(2-hydroxy-2-methylpropionyl)phenoxyacetamide
4-(2-hydroxy-2-methylpropionyl)phenoxyacetohydrazide
N-[4-(2-hydroxy-2-methylpropionyl)phenoxyacetyl]hydroxylamine

N-{4-(2-hydroxy-2-methylpropionyl)phenoxyacetyl]-N'-acryloylhydrazine
4-isocyanatomethoxyphenyl 2-hydroxy-2-propyl ketone
vinyl 4-(2-hydroxy-2-methylpropionyl) phenoxyacetate

## (11) AU-B-12624/88

(10) 608573

2-(2-hydroxyethylthio) thioxanthone

2-(2-aminoethylthio) thioxanthone

2-{2-(acryloyloxy) ethylthio} thioxanthone

2-{2-(acryloylamino) ethylthio} thioxanthone

2-{2-(allyloxy) ethylthio} thioxanthone

2-[2-(allylamino) ethylthio] thioxanthone

2-[2-(6-isocyanatohexylaminocarbonyloxy) ethoxy] thioxanthone

2-(oxiranylmethoxy) thioxanthone

2-{3-(triethoxysilyl) propoxy} thioxanthone

\* :-

### **AUSTRALIA**

#### PATENTS ACT 1952

### COMPLETE SPECIFICATION

(ORIGINAL)

608573

FOR OFFICE USE

Application Number: Lodged:

Complete Specification Lodged: Accepted:

Published:

Publishe

This document contains the amendments made under Section 49 and is correct for printing

Priority: Related Art:

### TO BE COMPLETED BY APPLICANT

Name of Applicant:

MERCK PATENT GESELLSCHAFT MIT

BESCHRÄNKTER HAFTUNG

Address of Applicant:

Frankfurter Strasse 250, D-6100 Darmstadt, Germany

Actual Inventors:

Dr. Manfred Köhler
 Dr. Jörg Ohngemach
 Dr. Eike Poetsch

Dr. Rudolf Eidenschink
 Prof. Dr. Gerhard Greber

6. Dr. Dieter Dorsch
7. Dr. Jürgen Gehlhaus
8. Dr. Konrad Dorfner
9. Dr. Hans-Ludwig Hirsch

Address for Service:

ARTHUR S. CAVE & CO.

Patent & Trade Mark Attorneys

Level 10

10 Barrack Street SYDNEY N.S.W. 2000

**AUSTRALIA** 

Complete Specification for the invention entitled CORERCTIVE PHOTOINITIATORS.

The following statement is a full description of this invention including the best method of performing it known to me:-



.... 20

25

30

- 2 -

The invention relates to coreactive photoinitiators or chotopolymerization of systems containing ethylenically disaturated compounds.

Photochemically induced polymerization reactions have taken on great importance in industry, in particular when rapid hardening of thin layers is important, such as, for example, on hardening of paint and resin coatings on paper, metal and plastic, or on drying of printing inks, since these processes are distinguished compared to conventional methods of printing and souting objects through a saving in raw materials and energy and less environmental pollution. However, the preparation of polymer materials per se through polymerization of appropriate unsaturated monomeric starting materials is also frequently curried out photochemically, it being possible to use conventional processes such as solution and emulsion solymerization.

Since, in the reactions mentioned, none of the reactants is generally capable of absorbing the photochemically active radiation to an adequate extent, it is necessary to add so-called photoinitiators which are capable of either absorbing incident high-energy radiation, usually UV light, to form active starter radicals, which themselves initiate the photopolymerization, or of transferring the absorbed energy to one of the polymericable reactants for free-radical formation. The initiations do not normally participate in the actual polymerication reaction.

The major initiators which have hitherto been closed for photopolymerization of unsaturated compounds the benzophenone derivatives, benzoin ethers, benzil kerais, dibenzosuberone derivatives, anthraquinones,

tanthones, thioxanthones, a-haloacetophenone derivatives, dialkoxyacetophenones and hydroxyalkylphenones.

As is known, however, the industrial applicability of tany of the substances mentioned is Limited, in some cases considerably, by a number of disadvantages. These include, in particular, a frequently unsatisfactory reactivity in the ability to initiate photopolymerization of ethylenically unsatura d compounds. Besides moleculespecific reactivity, the solubility or the ability of the 10 photoinitiators to be incorporated as homogeneously as cossible into the photopolymerizable systems frequently clays a crucial role here.

Further problems are the dark-storage stability of the systems to which photoinitiators have been added and 15 the possible influencing of the final product by radicals or degradation products of the photoinitiator. Such radicals can lead to a more or less pronounced effect on the product's properties, depending on the nature and quantity. In photopolymerized paint coatings, the major area of 20 application for photoinitiators, for example, such radicals can affect the final achievable hardness of the coating; in addition, undesired colour changes, for example yellowing, can occur, often only after a relatively long time. Initiator radicals or degradation products chereof can become 25 noticeable due to an unpleasant odour as a consequence of their more or less pronounced volatility; their diffusion from the coating into the surrounding media can cause problems, for example in packaging materials which are provided with photopolymerized loatings, such as, for example, 30 cans and tubes for foods. It is precisely in this area of apolication that the question of applicability is definitively determined by the possible or proven toxicity of tre photoinitiators and the degradation products thereof.

A particular problem, above all with respect to 35 broad application of photoinitiators, is that they can, n surally, only be employed in systems which essentially c. (2) components having olefinic double bonds which can be solymerized by means of free radicals.

Thermocurable systems based exclusively on polyaddition or polycondensation reactions which are not induced by free radicals cannot be converted into radiationcurable systems by adding free radical-forming photoinitiators. Accordingly, the choice of materials for components for radiation-curable systems is limited. Hany materialspecific properties of thermocurable systems cannot or cannot yet be used in radiation-curable systems without curther action. One alternative here is provided by so-10 called hybrid binder systems, in which thermocurable and photochemically curable components are combined and in which the thermal and photochemical reactions can take place simultaneously or successively. However, compatibility problems, in particular with respect to the photoinitiators to be employed frequently arise during development of such systems. Thus there continued to be a particular demand amongst experts for photoinitiators which, besides excellent initiator properties and good dark storage stability of the systems to which they have been ....: 20 added, also have a broad applicability, even in systems with a complex composition, and which can themselves, or their photolysis products, be bound in such systems in a migration-resistant manner.

Individual steps in this direction have already
then taken. Thus, for example, German Offenlegungsschrift
3,534,645 and European Offenlegungsschrift 161,463 describe
photoinitiators of the hydroxyalkylphenone type which
carry specifically olefinically unsaturated substituents.
These initiators or their photolysis products can be bound
into the polymer composition by copolymerization with the
components of the radiation-curable system. They can
alternatively initially be thermally polymerized themselves and then, as polymeric and as migration-resistant
photoinitiators, introduced into the radiation-curable
system. However, these specific copolymerizable or
polymeric photoinitiators have an only limited range of
applications.

The invention thus had the object of finding and

- 5 -

providing photoinitiators which, if possible, should be structured so that, besides the ability to initiate polymerization of ethylenically unsaturated compounds by means of the action of radiation, they also have the procenty of reacting with any desired components of radiation-curable systems, irrespective of whether these participate in the photopolymerization reaction or not, with the aim of stable binding into the resultant polymer composition.

It has now been found that this is achieved in an excellent fashion by compounds of the general formula I

IN) is a photoinitiator basic structure

where

$$R = 1$$
  $R^2$   $-CR^3R^4R^5$  or  $-P(R^6)_2$ 

 $R^{1}$  is H,  $C_{1-12}$ -alkyl, halogen or the RG-A- group, or two R<sup>1</sup> radicals in the ortho position to the carbonyl group together are alternatively -S-,

 $R^2$  is H, halogen,  $C_{1-12}$ -alkyl or  $C_{1-12}$ -alkoxy or the RG-A- group,

in each case independently of one another R<sup>3</sup> R<sup>4</sup> are H, C1-12-alkyl, C1-12-alkenyl, C1-12alkoxy or phenyl, or together are C2-6alkylene,

 $R^{5}$  is  $C_{1-6}$ -alkyl,  $C_{1-6}$ -alkanoyl, phenyl or benzoyl, each of which is optionally substituted by halogen, C<sub>1-6</sub>-alkyl or C<sub>1-6</sub>-alkoxy,  $R^7$  is H,  $C_{1-6}$ -alkyl or  $C_{1-6}$ -alkanoyl,

:0

35

•

is a spacer group {[(CH<sub>2</sub>)<sub>o</sub>x]<sub>n</sub>-[(CH<sub>2</sub>)<sub>m</sub>x]<sub>[</sub>

T, Y and Z, in each case independently of one another, are a single bond, -0-, -S-, -NH-, -CO-, -CO-, -NH-CO- or -NH-COO-,

(;)

I and m are the numbers 1 to 4, n and o are the numbers 0 to 4 is one of the functional reactive groups HO+, HS+, H2N+, halogen, HO+CO+, H2N+CO+, O=C=N+, S=C=N+, N3+, SO3H, SO2Cl;  $R^{C}R^{D}C=CR^{3}$ + where  $R^{3}$ ,  $R^{b}$  and  $R^{C}$  are in each case H or CH3, and with the proviso that Z is not +COO+ when n is 0 and  $R^{5}$  is  $OR^{7}$ ; RG is furthermore halogen, cyclopropyl, oxiranyl,  $O=C=N-R^{d}$  where  $R^{d}$  is  $C_{1-6}$ -alkylene or phenylene,  $N_{2}$ +  $C_{1-12}$ -alkoxy or  $C_{1-12}$ -alkanoyloxy-

Some of the compounds of the formula I are new. These are highly reactive photoinitiators which, irrespective of their photoreactivity, can enter into non-photochemically induced (co)reactions and are therefore to be called coreactive photoinitiators.

In the context of the invention, coreactions are to be understood as all reactions which the photoinitiators or the photolysis products thereof enter into with components of radiation-curable systems, with themselves or alternatively with the substrate to which these or an appropriate radiation-curable system is applied as a paint or coating, and which cause fixed-location bonding of the photoinitiators or the degradation products thereof. These coreactions are primarily reactions in which covalent chemical bonds are made. However, reactions are also possible in which the fixing action is based on other interactions, such as, for example, ionic or polar interactions.

35

The particular advantage of the compounds according to the invention over conventional photoinitiators arises from the presence of the reactive RG group, which is linked to spacer group A and which, in addition to specific

undivided in the second of the actual photoreaction before, during or after the latter.

Surprisingly, this leads to an unexpectedly large ext of incorporation of the unreacted photoinitiators of the unreacted photoinitiators of the polymer product which is finally obtained. This very effectively allows undesired influences on the properties of the final product to be reduced or entirely eliminated.

In addition, fixing of photoinitiators directly to the substrate or in the form of a coating of oligomeric, polymeric or copolymerized photoinitiators offers better anchoring of photopolymerizable coatings applied to the latter to the substrate or better coating hardening due of initiator concentrations which are particularly high locally. In this application, in particular, interesting effects and new properties can be achieved.

Many compounds of the formula I are, in addition, valuable synthesis intermediates on the route to further functionalized photoinitiators or radiation-reactive systems having a covalently bound photoinitiator.

The invention thus relates to the use of the concounds of the formula I as coreactive photoinitiators for photopolymerization of systems containing ethylenically unsaturated compounds, in particular in the radiation curing of coatings having UV-curable paint and binder systems, above all also hybrid binder systems.

The invention also relates to compounds of the ormula I per se, so long as they are new.

The invention furthermore relates to a process for shotopolymerization of systems containing ethylenically ensaturated compounds, at least one compound of the formula I being added as a coreactive photoinitiator to the sture before initiation of the photopolymerization.

In addition, the invention relates to photo-

•

....: 20

.... 15

10

25

30

exymerizable systems containing at least one ethylenically in iterated, photopolymerizable compound and, if appropriate, further known and conventional additives, the systems containing at least one compound of the formula I containing at least one compound of the formula I

Finally, the invention relates to the use of community of the formula I as synthesis intermediates in the preparation of further-functionalized photoinitiators and of radiation-reactive systems having a covalently bound observable interaction.

The compounds of the formula I are structurally derived from known photoinitiators. In the formula I, IN is any photoinitiator structure, which is linked to a functional reactive group RG via a spacer group A, which can, in principle, likewise be any spacer group.

In the compounds of the formula I, photoinitiator properties of structural part IN are thus combined with the n-n-photochemically induced reactivity i.e. coreactivity, of structural part RG.

IN is essentially the aromatic ketone structural

. it

...: 20

25

30

-C-R

as is present in virtually all classical photoinitiators, but can alternatively be any other structures having photoinitiator properties.

If, in the aromatic ketone structural unit R is an optionally substituted chenyl ring, the result is optionally substituted chenyl ring, the result is optionitiators of the benzophenone series. If, in this is, two R<sup>1</sup> radicals which are ortho to the carbonyl group ther form a sulfur bridge between the phenyl rings, result is thioxanthone photoinitiators. Coreactive to exanthone derivatives are particularly preferred photoinitiators in the context of the invention.

If R is the  $\frac{-CR^3R^4R^5}{4R^5}$  group with the abovementioned definitions for  $R^3$ ,  $R^4$  and  $R^5$ , the result is the photo-ir liator basic structures of benzoin and acyloin ethers,

10

30

- 9 -

entil ketals and dialkoxyacetophenones, hydroxyalkylanenones and aminoalkylphenones, and a-sulfonylketones. Coreactive hydroxyalkylphenone derivatives are twise particularly preferred photoinitiators in the cortext of the invention.

If R is the P(R<sup>6</sup>)<sub>2</sub> group, the resulting photoinitiators belong to the class of the acylphosphine oxides. The spacer group: A linking the photoinitiator basic of the tune IN to the reactive functional group RG preferably has the structure ZE(CH<sub>2</sub>)<sub>0</sub>YI<sub>0</sub>-E(CH<sub>2</sub>)<sub>n</sub>XI<sub>1</sub>.

In the simplest case, when X, Y and Z are each a single bond, the spacer group is an alkylene bridge, preferably having 1 to 8 carbon atoms. Such an alkylene broup can also be linked to the aromatic ring of the photoinitiator basic structure via a heteroatom when X is -x-. -S- or -NH-.

However, the alkylene bridge may also be interted by one or more heteroatoms, which is the case when is -0-, -S- or -NH-. Interruptions of the alkylene ridge by carbonyl, carboxyl, carboxamide or urethane roups are also possible. Thus, for example, one or more axy-, this or aminoalkylene groups, preferably oxyethylene and thioethylene can function as spacers. Mixed heteroakylene bridges, in particular those containing oxygen and sulfur as heteroatoms are likewise possible. Depending on the chemical nature of the functional reactive group RG, the latter is linked to the spacer group in accordance with the definitions where Z is a single bond, -0-, -S-, -NH- or a carboxyl group or a derivative the effective and such as a carboxamide or urethane group.

Suitable reactive groups RG are all functional twos which are easily able to enter non-photochemically address reactions. The aim of each such reaction is to bind the photoinitiator or photolysis products thereof to the system at a fixed location. Such reactions can be, for example, nucleophilic substitutions by or consely on the RG group such as, for example,

:0

••. •

• • • • •

· . . :

.....2

2 .

30

respectively. Experience of the system which train functional groups having acidic H atoms.

Preferred reactive RG groups are likewise those which are able to undergo thermally initiated free-radical or ionic polymerization, polyaddition or polycondensation reactions. These include the vinylogroup and the mono- or olymethylated analogues thereof, and the cyclopropyl and rin myl groups. Isocyanate-functionalized Congralkyl rougs or phenyl groups are examples of groups which are lapable of polyaddition. Insertion reactions into any dasired components of the system can be accomplished by generating carbones or free radicals, for example by means of the azide group as the reactive RG group. For covalent conding, the typical reactions of the diazonium group are also suitable. Besides polysiloxane formation, the silyl ;roup offers, in particular, the possibility of covalent linking to the substrate, especially when the latter is of an inorganic nature such as, for example, glass, ceramic or metal. In accordance with the definitions given for the photoinitiator basic structure IN, the spacer A and the reactive RG group, numerous coreactive photoinitiators ing properties which are customized for a very wide ariety of applications and purposes can be achieved through combination.

The compounds of the general formula I can be meaned by standard methods of organic chemistry. The factions conditions here can be taken from standard works in preparative organic chemistry, for example, HOUBEN-VEYL, the talen der organischen Chemie, (Methods of Organic

20

2 :

35

- ii -

Inemistry), Georg-Thieme Verlag, Stuttgart, or ORGANIC HESIS, J. Wiley, New York London Sydney.

It is generally favourable to prepare the photoin tiators according to the invention, or the precursors thereof, by proven synthetic methods, as are common for the known photoinitiators.

In this preparation it is advantageous to proceed directly from the known photoinitiators as starting materials and to link the spacer group A and the reactive subgroups. So RG to these in one or more steps using common resctions, such as substitution reactions. However, precursors of known photoinitiators which are already suital substituted can also be used and the actual photoinitiator active structure be generated in these only when the spacer and reactive groups are already present.

The compounds of the general formula I can be used according to the invention as photoinitiators for photopolymerization of ethylenically unsaturated compounds or ar suring photopolymerizable systems which contain such papounds, and, in particular, also as UV hardeners for paint coatings, UV-curable binder and hybrid binder valens, printing inks and in radiation curing of aqueous repolymer dispersions. This use takes place in a conventional fashion. The compounds to be used according to the invention are generally added to the systems to be polymerized in amounts from 0.1 to 20% by weight, preferably 3.5 to 12% by weight.

This addition generally takes place by simple dissolving and stirring in since most of the photo-initiators to be used according to the invention are liquid or at least readily soluble in the systems to be polymerized. A system to be polymerized is taken to mean aixture of mono- or polyfunctional ethylenically unsaturated monomers, oligomers, prepolymers, or polymers, or sixtures of these oligomers, prepolymers and polymers with unsaturated monomers, which can be initiated by free icals, it being possible for the mixture to contain, accessary or desired, further additives, such as, for

example, antioxidants, light stabilizers, colorants and partents, but also further known photoinitiators and reare on accelerators. Suitable unsaturated compounds are at those whose C=C double bonds are activated by, for ecc. le, halogen atoms, carbonyl, cyano, carboxyl, ester, amile, ether or aryl groups or by conjugated further double or triple bonds. Examples of such compounds are vinyl chloride, vinylidene chloride, acrylonitrile, methacryloorrile, acrylamide, methacrylamide, methyl, ethyl, n- or ters, butyl, cyclohexyl, 2-ethylhexyl, benzyl, phenoxyether, hydroxyethyl, hydrox propyl, lower alkoxy ethyl, and tetrahydrofurfuryl acrylate or methacrylate, vinyl acetate, propionate, acrylate and succinate, N-vinyl pyrrolidone, N-vinylcarbazole styrene, divinylbenzene, subscituted styrenes and mixtures of unsaturated compounds of linese types. Polyunsaturated compounds, such as, for example, ethylene diacrylate, 1,6-hexamedial diacrylate, arapoxylated bisphenol A diacrylate and dimethacrylate, comethycolpropane diacrylate and pentaerythritol triacrilate, can also be polymerized with the photoinitiators used according to the invention. Suitable photopolymerizable compounds are, in addition, unsaturated oligomers, orepolymers or polymers, and mixtures thereof, with unsaturated monomers. These include, for example, unsaturated polyesters, unsaturated acrylic materials, epoxy materials, urethanes, silicones, aminopolyamide resins and, particularly, acrylated resins, such as acrylated silicone oil, acrylated polyesters, acrylated urethanes, acrylated polyamides, acrylated soybean oil, acrylated epoxy resin and acrylated acrylic resin, expediently in a mixture with He or more acrylates of a mono-, di- or polyalcohol.

The photopolymerizable compounds or systems can be stabilized without thereby appreciably impairing the initiator action of the photoinitiators according to the ir ention by adding known thermal inhibitors and antioridants such as, for example, hydroquinone or hydroquinone erivatives, pyrogallol, thiophenols, nitro compounds, in shthylamines or B-naphthols, in conventional amounts.

30

5

. 0

15

. . . :

. . 20

111111111

75

į

:0

15

. 50

such additions are intended, above all, to prevent premature polymerization during production of the systems through mixing of the components.

In addition, small amounts of light stabilizers are as, for example, benzophenone derivatives, benzo-triarole derivatives, tetraalkyloiperidines or phenyl sali ylates, can be added.

In order to exclude the inhibiting action of atmospheric oxygen, paraffin or similar waxy substances are frequently also added to photopolymerizable systems. As a consequence of poor solubility in polymers, these float at the beginning of the polymerization and form a terminarent surface layer which prevents entry of air. It is opossible to deactivate the atmospheric oxygen, for when e by introducing autooxidizable groups, such as, for example allyl groups, into the system to be cured.

The photoinitiators according to the invention can also be used in combination with known free-radical initiators such as, for example, peroxides, hydroperzides, ketone peroxides or percarboxylates. In addition, they can contain pigments or dyes, as are customary, for example, in photochemically curing printing inks. In this case, the amount of photoinitiator is chosen to be higher, for example 6 to 12% by weight, whereas 0.1 to 5% by reight are fully sufficient in most cases for colourless photopolymerizable products. Depending on the intended application, fillers, such as talc, gypsum or silica, fibres, organic additives, such as thixotropic agents, levelling agents, binders, lubricants, flatting agents, :lasticizers, wetting agents, silicones for improving the surface quality, antifloating agents or minor amounts of olvents can be added.

Suitable known photoinitiators which can be used, faporopriate, together with the initiators according to the invention, are, for example, benzophenones, such as, for example, Michler's ketone [4,4'-bis(dimethylamino)-benzophenone, photophenone, photophenone, photophenone and

ic

.... 15

.....: 20

25

30

pen-ophenone: anthraquinones, such as, for example, archraguinone, 2-chloroanthraguinone and 2-alkylanthraqui ones; kanthones, such as, for example 2-haloxanthones or 2-m.kylxanthones; thioxanthones, such as 2-chlorothioconthone and 2-alkylthioxanthones; acridanones, such as, for example, 2-alkylacridanones or N-substituted acridanores; benzoins, such as, for example, p-dimethylaminoberrain and alkyl ethers of benzoin; benzil ketals, aha oketones, dialkoxyacetophenones, a-hydroxyalkylphenones and a-aminoalkylphenones, as described, for example, in German Offenlegungsschrift 2,722,264 and European Offenlegungsschrift 3,002, and furthermore, for example, fluorenones, dibenzosuberones, phenanthrenequinones and berroates, such as, for example, hydroxypropyl benzoate and benzoyl benzoate acrylate. Mixtures with known initisters generally contain the coreactive photoinitiators to . a used according to the invention in proportions of at least 10% by weight, advantageously from 50 to 95% by weight relative to the total amount of the initiator mixture employed.

Besides the photoinitiators according to the invention, it is advantageous to employ reaction accelerators in the photopolymerizable systems. Examples of such comcounds which can be added are organic amines, phosphines, alcohols and/or thiols all of which have at least one CH group in the a position to the heteroatom. For example, primary, secondary and tertiary aliphatic, aromatic, araliphatic or heterocyclic amines, as described, for example, in U.S. Patent 3,759,807, are suitable. Examples of such amines are butylamine, dibutylamine, triutylamine, cyclohexylamine, benzyldimethylamine, dicycloherylamine, triethanolamine, N-methyldiethanolamine, henyldiethanolamine, piperidine, piperazine, morpholine, pyridine, quinoline, ethyl p-dimethylaminobenzoate, butyl --dimethylamino benzoate, 4,4'-bis(dimethylamino)nzophenone (Michler's ketone) or 4,4'-bis(diethylamino)i-izoohenone. Particular preference is given to tertiary .: nes such as, for example, trimethylamine, triisopropyl-

.....: 20

amine, tributylamine, octyldimethylamine, dodecyldimethylamine, triethanolamine, N-methyldiethanolamine, N-butylati-thanolamine, tris(hydroxypropyl)amine, and alkylditet.ylamino benzoate. Further examples of suitable reaction accelerators are trialkyl phosphines, secondary alcohol and thiols. The addition of reaction accelerators of these types can take place in amounts which are conventional for them.

Photopolymerizable systems which additionally 10 con ain a tertiary organic amine as reaction accelerator represent a particularly preferred form of the present invention.

The term "photopolymerization of ethylenically unsaturated compounds" should be understood in the broadest 15 serie. It also includes, for example, further polymerization or crosslinking of polymeric materials, such as inspectymens, the homo-, co- and terpolymerization of simple managers and also the combination of the types of reaction tentioned.

The photopolymerization can be initiated through the action of high-energy irradiation, preferably UV light, on the photopolymerizable systems, containing coreactive photoinitiators according to the invention. The photopolymerization takes place by methods which are known per se, through irradiation with light or UV irradiation in the 44/elength range from 250 to 500 nm, preferably 300-400 nm. Irradiation sources which may be used are sunlight or artificial-light lamps. Mercury high-pressure, medium-pressure or low-pressure lamps and xenon and tungsten lamps, for example, are advantageous.

The photopolymerization using the photoinitiators according to the invention can be carried out either stables or continuously. The duration of irradiation depends on the way in which the photopolymerization is alterial out, on the type and quantity of polymerizable raterials employed, on the type and concentration of the continuously, and on the intensity of the light succe and can be in the range from several seconds to

minutes, such as, for example, on irradiation curing of patings, but may also be in the hours region in the case of targe batches such as, for example, in bulk polymerization.

The compounds of the formula I according to the envention are preferably used as photoinitiators in UV curare of thin coatings such as, for example, paint coatings, on all materials and substrates which are conventional for this. These can primarily be paper, wood, textile substrates, plastic and metal. An important area of applica-10 tion is also the drying or hardening of printing inks and screen printing materials, of which the Latter are preferable employed in surface coating or shaping of, for excaple, cans, tubes and metal sealing caps. As a consequence of he substantial to complete absence of free initiator 15 rac cals after photopolymerization has taken place in systems to which coreactive photoinitiators according to the invention have been added, the systems are particularly suitable in areas of application where diffusion of such cadicals into media surrounding the corresponding final TO products is to be excluded, for example when packaging which is provided with photopolymerized coatings comes into contact with foodstuffs.

The essential classes of the coreactive photoinitiators according to the invention, typical representatives and the preparation and preferred manner of use thereof are shown below.

Compounds of the subformula II

having the abovementioned meanings for the particular substituents essentially represent the particularly preferred areactive photoinitiators of the hydroxyalkylphenone type  $^{\tau}$  and  $^{\tau}$  are  $^{\tau}$  are  $^{\tau}$  also alkylphenone type enone type ( $^{\tau}$  is, if appropriate, also alkylsubstituted mino), and in addition coreactive derivatives of benzoin ethers ( $^{\tau}$  is phenyl,  $^{\tau}$  is H,  $^{\tau}$  calkyl or phenyl,  $^{\tau}$ 

:

5

10

30

3:

:  $C_{1-12}$ -alkoxy), benzit ketals ( $R^3$  is phenyl,  $R^4$  and  $R^5$  are  $C_{1-12}$  alkoxy) and dialkoxyacetophenones ( $R^3$  is H,  $C_{1-12}$ -alkyl,  $R^4$  and  $R^5$  are  $C_{1-12}$ -alkoxy).

Besides the functionalization of conventional chotoinitiators which are commercially available or can be prepared by known methods, particular importance is attached in the preparation of compounds of the formula II, in particular in the preferred hydroxyalkylphenone and amountalkylphenone derivatives, to the preparation from appropriately substituted precursors on which the photoinitiators are based, an analogous procedure to methods thich are known for this purpose being followed. These eth ds are described in detail, for example, in German offentegungsschrift 2,722,264 and European Offentegungsschrift 3,002. Coreactive hydroxyalkylphenone derivatives can be obtained, for example from suitable phenyl derivatives which already contain the spacer group A and the actional group RG or appropriate precursors, by carrying t a Friedel-Crafts acylation using an appropriate acyl valide in order to introduce the active photoinitiator structure or a precursor thereof. Phenyl derivatives which can be employed as suitable starting materials are, for example, phenol, phenyl thiol, phenoxyacetic acid and sonoor polyethoxylated phenol, such as 2-hydroxyethyl pheny! ether. For the friedel-Crafts acylation, it is advisable in some cases to protect the terminal functional groups by suitable protecting groups which can be removed later, such as by acylation in the case of the OH group. Aniline derivatives can be acylated under Vilsmeier conditions, or example using N,N-dimethylisobutyramide and phosphorus exychloride.

In order to produce the active photoinitiator structure of the hydroxyalkyl phenone type, an acylation can be carried out, for example, using isobutyryl halide or archloroisobutyryl halide and subsequently introducing the recoxyl, alkoxy or alkanoyloxy group. Thus, for example, cried i-Crafts acylation of acylated 2-hydroxyethyl phenyl her using isobutyryl chloride and subsequent bromination

10

25

-- hydrolysis on the tertiary carbon atom leads to the appound 4-(2-hydroxyethoxy)phenyl 2-hydroxy-2-propyl

The compound IIa, which has already been described set se and as a photoinitiator for aqueous systems in German Offenlegungsschrift 3,512,179 is of central importance tere since, due to the terminal OH group, it is capable, on the one hand, of coreactivity in the sense of the invention, but, on the other hand, can also serve as an intermediate for a large number of further coreactive photoinitiators which are derived from this and which contain other functional groups.

This compound is also especially suitable as a .:reactive photoinitiator in hybrid binder systems. Such systems very generally contain at least one-thermocuring component and one photochemically curing component. The thermocuring component is normally a two or multicomponent reaction resin, preferably of the polyol/polyisocyanate type. Suitable photochemically curing components are all achomeric, oligomeric or polymeric unsaturated compounds which are conventional for this purpose, and combinations therrof, whose polymerization or crosslinking takes place through the influence of high-energy irradiation and with the aid of the photoinitiator. Such hybrid systems can be obtained by mixing all the components, the isocyanate comconent, as usua' for polyurethane-forming reactive resins, xpediently not being added until just before use in order to prevent premature curing of the thermopolymerizing supponent. Coatings produced using such hybrid systems are ered by initially irradiating them in a fashion which is conventional for radiation-curing systems, rapid surface fiving and curing of the coating being achieved. The fully used state is reached after completion of the thermal . ction, which can also be accelerated by applying heat.

10

15

30

The advantage of these systems over slow-drying systems on a purely thermal reactive resin basis is the considerable saving in time and energy; the coated articles can be searched immediately or further processed more quickly.

The advantage of the coreactive pnotoinitiators according to the invention, such as compound IIa, on use in Sprid binder systems is that, in contrast to conventional photoinitiators, virtually no photoinitiator residues or photolysis products thereof can be detected in the fully cured polymer material, as shown by extraction experiments. Accordingly, the polymer products exhibit a relatively high final hardness. Adverse effects due to the initiator such as, for example, odour or yellowing, are not observed. Due to the coreactive OH group, the photoinitiator according to the invention is incorporated covalently into the polymer material through reaction with equivalent amounts of the isogenate component of the thermally curing component in the hybrid binder system.

Compound IIa can also be fixed covalently in both purely radiation-curable systems and in hybrid systems through esterification by means of carboxylic acid group-containing components. Examples of such components are, for example, terephthalic acid, pyromellitic acid and anhydrides thereof, and oligomers or polymers which are derived from these compounds and contain at least one free carboxylic acid function.

Coreactive photoinitiators according to the invention which are derived from compound IIa are, for example:

4-[2-(oxiranylmethoxy)ethoxy]phenyl 2-hydroxy-2-propyl ketone

$$CH_2-CH-CH_2-O-CH_2CH_2-O-CH_2CH_3$$

$$CH_3$$

$$CH_3$$

$$CH_3$$

$$CH_3$$

$$CH_3$$

--(2-allyloxyethoxy)phenyl 2-hydroxy-2-propyl ketone

--(2-(3-triethoxysilylpropoxy)ethoxy]phenyl 2-hydroxy-2propyl ketone

$$(C_2H_5O)_3Si-(CH_2)_3-O-CH_2CH_2-O-C-C-OH$$
 (IId)

4-(2-aminoethoxy)phenyl 2-hydroxy-2-propyl ketone

$$H_2N-CH_2CH_2-O-CO-COH$$

$$CH_3$$

$$CH_3$$

$$CH_3$$

$$CH_3$$

.-(2-azidoethoxy)phenyl 2-hydroxy-2-propyl ketone

.... 10

15

30

The compounds IIb and IIc can be obtained from IIa through reaction with epichlorohydrin or allyl bromide. Compound IId can be obtained from IIc through subsequent reaction with triethoxysilane.

Compound IIe can be prepared, for example, by hydrogenation of II<sup>2</sup>.

Compound IIf is obtained by reacting the ptoluenesulfonate of IIa with sodium azide.

The epoxy-functionalized photoinitiator IIb can advantageously be employed, in particular, in hybrid binder systems whose thermocurable component is a reactive resin of the epoxy type. Due to the epoxy function, IIb or its photolysis products are bound virtually completely into the army polymer of the binder system.

ιċ

25

30

The photoinitiator (IC which is functionalized with an unsaturated component can be copolymerized with unsaturated components of any radiation-curable compositions. It can also be thermally polymerized itself. The resultant compositions, where it remains migration-resistant, due to it; colymeric character. It can also be initially applied on.v as a polymeric initiator coating to a substrate. A phonorurable paint coating which is applied on top and which does not require any further addition of initiator can then be cured with excellent substrate adhesion.

The sityt-functionalized initiator IId can be employed in an analogous fashion, its use bringing advantages primarily in the coating of inorganic substrates such as metals, glass or other silicate materials, due to the adhesion-improving sityt groups.

Compound IIe can be employed analogously to IIa; compound IIf is highly reactive due to the azido group and is capable, for example, of insertion reactions.

The carboxylic acid-functionalized photoinitiator 4-(hydroxycarbonylmethoxy)phenyl 2-hydroxy-2-propyl ketone

attows fixing by reactions which are typical of carboxylic acids such as salt formation, esterification, acid amide formation etc. Fixing by esterification with macromolecular polyhydroxyl compounds, such as cellulose and related materials is particularly important.

In materials which have been modified in this fashion, a very high initiator concentration is achieved at the surface which is very advantageous for subsequent further modification using photopolymerizable materials, such as in photoinitiated grafting of monomers "photografting").

The following coreactive photoinitiators can be

prepared in an analogous fashion and can be used like the abovementioned compounds:

4-ollyloxyohenyl 2-hydroxy-2-propyl ketone

5 4-oxiranylmethoxyphenyl 2-hydroxy-2-propyl ketone

4-[3-(triethoxysilyl)propoxy]phenyl 2-hydroxy-2-propyl

ketone

$$(c_2 E_5 o)_3 si - (CE_2)_3 - o - \bigcirc -c - c - o E_5$$
 $(CE_3)_3 si - (CE_2)_3 - o - \bigcirc -c - c - o E_5$ 
 $(CE_3)_3 si - (CE_2)_3 - o - \bigcirc -c - c - o E_5$ 

-- C2-(3-triethoxysilylpropylthio)ethyl]phenyl 2-hydroxy-2-propyl ketone

$$(c_2H_5O)_3Si-(CH_2)_3-S-(CH_2)_2 -c-c-OH_1$$

4-(2-chloroethoxy)phenyl 2-hydroxy-2-propyl ketone

4-(cxiranylaethoxycarbonylmethoxy)phenyl 2-hydroxy-2-propyl kitone

4-oxiranylaethoxyphenyl a-isopropoxybenzyl ketone

4-[3-(triethoxysityt)propoxy]phenyt  $\alpha$ -isopropoxybenzyt ketone

$$(c_2H_5O)_3Si-(CH_2)_3-O-\underbrace{\begin{array}{c} 0 & O-CH(CH_3)_2 \\ " & I \\ -C-CH- \end{array}}_{(IIO)}$$

4-oxiranylmethoxyphenyl a,a-dimethoxybenzyl ketone

4-{3-(triethoxysilyl)propoxy]phenyl a,a-dimethoxybenzyl

$$(c_2H_5O)_3Si-(CH_2)_3-O-$$

$$\begin{array}{c} O & OCH_3 \\ -C-C-C \\ O & OCH_3 \end{array}$$
(119)

4-(2-isocyanatoethoxy)phenyl 2-hydroxy-2-propyl ketone

4-(2-isothiocyanatoethoxy)ohenyl 2-hydroxy-2-propyl ketone

4-(2-hydroxy-2-methylpropionyl)phenoxyacetamide

4-(2-hydroxy-2-methylpropionyl)phenoxyacetohydrazide

N-(4-(2-hydroxy-2-methylpropionyl)phenoxyacetyl]-hydroxylamine

5

N-[4-(2-hydroxy-2-methylpropionyl)phenoxyacetyl]-N'-acryloylhydrazine

$$\begin{array}{c} \text{CH}_3 & \text{O} \\ \text{EO-C} & \text{C-} \\ \\ \text{CH}_3 \end{array} = \begin{array}{c} \text{O-CH}_2 - \text{CO-NENH-CO-CE=CH}_2 \\ \\ \text{CH}_3 \end{array}$$

4-isocyanatomethoxyphenyl 2-hydroxy-2-propyl ketone

vinyl 4-(2-hydroxy-2-methylpropionyl)phenoxyacetate

Compounds of the subformula III

$$RG-A \longrightarrow C \qquad C \qquad C \qquad (III)$$

15 having the abovementioned meanings for the respective substituents represent the likewise particularly preferred coreactive photoinitiators of the thioxanthone type.

Starting materials for these are commercially

(-(2-hydroxy-2-methylpropionyl)phenoxyacetohydrazide

N-[4-(2-hydroxy-2-methylpropionyl)phenoxyacetyl]hydroxylamine

5

N-(4-(2-hydroxy-2-methylpropionyl)phenoxyacetyl]-N\*-acryloylhydrazine

4-isocyanatomethoxyphenyl 2-hydroxy-2-propyl ketone

vinyl 4-(2-hydroxy-2-methylpropionyl)phenoxyacetate

Compounds of the subformula III

$$RG-A \longrightarrow C$$

$$C$$

$$C$$

$$R^{2}$$

$$R^{2}$$

$$(!!!)$$

having the abovementioned meanings for the respective substituents represent the likewise particularly preferred coreactive photoinitiators of the thioxanthone type.

Starting materials for these are commercially

10

15

20

25

30

available thioxanthone photoinitiators, or derivatives thereof, which are predestined for simple introduction of the spacer group A and functional groups RG. Particularly suitable such starting materials are 2-chlorothioxanthone and 2-hydroxythioxanthone.

The hydroxyl-functionalized photoinitiator 2-(2-hydroxyethylthio)thioxanthone (IIIa) is obtained by reacting 2-chlorothioxanthone with, for example, 2-mercaptoethanol.

The amino-functionalized photoinitiator 2-(2-aminoethylthio)thioxanthone (IIIb) can be obtained in a similar fashion.

Both compounds can be employed entirely analogously to compound IIa as coreactive photoinitiators, in particular also in hybrid binder systems.

Compounds IIIa and IIIb, likewise entirely analogously to compounds IIa, can also in turn serve as the starting material for further coreactive photoinitiators having other functional groups. Thus, the photoinitiators 2-[2-(acryloyloxy)ethylthic]thioxanthone (IIIc) 2-[2-(acryloylamino)ethylthio]thioxanthone (IIId) 2-[2-(allyloxy)ethylthio]thioxanthone (IIIe) and 2-[2-(allylamino)ethylthio]thioxanthone (IIIf) which are functionalized by an unsaturated group can be obtained, for example, through reaction with acrylyl chloride or allyl bromide.

These compounds are highly suitable as photoinitiators which can be copolymerized with unsaturated components of radiation-curable compositions. However, they can also be thermally polymerized by themselves and used as polymeric photoinitiators as described for compound IIc.

Isocyanate-functionalized photoinitiators such as,
for example
2-[2-(6-isocyanatohexylaminocarbonyloxy)ethoxy]thioxanthone

.... 25

30

can be obtained by reacting illa with an equivalent amount of a diffocyanate. Covalent binding into the radiation—curable polymer system can take place through reaction of the isocyanate group with OH groups of the components. Use in hybrid binder systems which contain, as thermocurable component, a polyurethane-forming reactive system is particularly favourable. The isocyanate-functionalized photoinitiator can be mixed here with the isocyanate hardener of the reactive resin component, and this mixture can be used, as it were, as a "hybrid hardener".

In an analogous fashion, as described for the corresponding compounds of the subformula II, epoxy-, silyland carboxylic acid-functionalized thioxanthone derivatives can be obtained and correspondingly employed, such as, for example, the compounds 2-(oxiranylmethoxy)thioxanthone (!IIh) and 2-[3-(triethoxysilyl)propoxy]thioxanthone (!IIi). Example 1

20 4-(2-Hydroxyethoxy)phenyl 2-hydroxy-2-propyl ketone (IIa)

a) 336 g (3.2 mol) of isobutyryl chloride are added dropwise over the course of 40 minutes while stirring to 880 g (8.8 mol) of anhydrous aluminium chloride in 480 ml of dichloromethane at -5 to 0°C. 540 g (3.0 mol) of 2-phenoxyethyl acetate are then added dropwise over the course of 2 hours at the same temperature. The reaction mixture is stirred for a further 2 hours at the stated temperature and then poured into a mixture of 1.8 l of concentrated hydrochloric acid and 5 kg of ice. The organic phase is separated off and the aqueous layer is extracted with dichloromethane. The combined organic phases are washed with water, dried and evaporated, and the residue is distilled in vacuo. 740 g of 4-(2-acetoxyethoxy)phenyl-2-propyl ketone of boiling point

145-152°C/0.3-0.5 torr are obtained.

b) 205 g (1.0 mol) of 4-(2-acetoxyethoxy)phenyl 2-propyl ketone are dissolved in 200 ml of glacial acetic acid, and 192 g (1.2 mol) of bromine are added over the course of 2 hours with stirring at 25°C. The mixture is then stirred for about a further 10 hours and then poured into 3 L of ice water. The product is extracted with ethyl acetate. The combined extracts are dried, and 365 g of a viscous oil are obtained by evaporation. This oil is dissolved in 1 l of ethanol, and 380 g of 32% strength sodium hydroxide solution are added over the course of 20 minutes with stirring at 25°C. The mixture is stirred for a further 10 minutes and the ethanol is then removed. The oily residue is transformed into 3 l of ice water, and this mixture is ext allow repeatedly with a total of 1.5 l of ethyl acetate. After drying, filtering and evaporating the solution, 250 g of an oily crude product are isolated. Through recrystallization from acetone/petroleum ether and/or chromatographic purification, 145 g of 4-(2-hydroxyethoxy)phenyl 2hydroxy-2-propyl ketone are obtained in the form of a colourless solid of melting point 88-90°C.

#### Example 2

5

10

15

30

35

4-(2-allyloxyethoxy)phenyl 2-hydroxy-2-propyl ketone (IIc)

26.8 g (0.22 mol) of allyl bromide and 1.8 g of methyltrioctylammonium chloride as phase-transfer catalyst are added to a mixture of 44.9 g (0.2 mol) of IIa and 8.8 g (0.22 mol) of granulated sodium hydroxide in 300 ml of toluene, and the mixture is stirred for 20 hours at 50°C. The mixture is then extracted with toluene. Conventional work-up and chromatographic purification give 28.5 g of the analytically pure compound IIc.

#### Example 3

4-[2-(0xiranylmethoxy)ethoxy]phenyl 2-hydroxy-2-propyl ketone ([[b])

Through reaction analogously to example 2, but using epichlorohydrin, compound IIb is obtained.

#### Ecample 4

4-72 (3-Triethoxysilylpropoxy)ethoxy]phenyl 2-Sydro y-2-propyl ketone ([[d])

5.3 g (0.02 mol) of compound IIc, 4.9 g (0.03 mol) of triethoxysilane and 20 mg of platinum catalyst (norborness) acetylacetonate complex) in 50 ml of methylene chickide are refluxed for 4 hours under nitrogen. After evaluation of the mixture and chromatographic purification of the residue, 3.4 g of the analytically pure compound IId are notained.

#### Estable 5

10

٥٠:....

25

30

35

4-(hydroxycarbonylmethoxy)phenyl 2-hydroxy-2-propyl ketone (IIg)

612 g of compound IIg of melting point 131-134°C are cutained analogously to Example 1 from 931 g (5.6 mol) of method phenoxyacetate by Friedel-Crafts acylation using 657 g (6.2 mol) of isobutyryl chloride and subsequent bromination and hydrolysis.

#### Example 6

4-(2-Hydroxy-2-methylpropionyl)phenoxyacetamide (iit)

75.0 g of 25% strength ammonia are added dropwise with stirring to 25.2 g (0.1 mol) of methyl 4-(2-hydroxy-2-methylpropionyl)phenoxyacetate (obtained by esterifying compound IIg using methanol) in 50 ml of dioxane. After being stirred for 2 hours, the mixture is evaporated to solidification. The crude product is recrystallized from hot water, 22.1 g of compound IIt of melting point 139°C being obtained.

## Example 7

4-(2-Azidoethoxy)phenyl 2-hydroxy-2-propyl ketone

37.8 g (0.1 mol) of 4-(2-p-tolylsulfonyloxyethoxy)-chenyl 2-hydroxy-2-propyl ketone (obtained by reacting compound IIa with p-toluenesulfonyl chloride) and 9.8 g (0.15 mol) of sodium azide are stirred for one hour in 100 ml of DMSO at 60°C. Through extractive work-up using water and ether or methyl t-butyl ether, 22.4 g ofcompound IIf

3.2 obtained as a pale yellow, readily mobile oil. (R:  $v=1.14-u^{-1}$  (N3).

#### Erano - 3

4-Altyloxyphenyl 2-hydroxy-2-propyl ketone (IIh) 5.6 g (0.22 mol) of sodium hydride (80% strength in parafrin oil) are added in portions to 36.0 g (0.2 mol) of 4-hydroxyphenyl 2-hydroxy-2-propyl ketone in 450 ml of dimethyl sulfoxide under an inert gas and the mixture is stir: I for 15 minutes at room temperature. 26.8 g (0.22 mol) of altyl bromide in 40 ml of dimethyl sulfoxide are then added dropwise at 30-40°C, and the mixture is stirred for f minutes. The reaction mixture is poured into 2 l of vate; and then extracted with methyl t-butyl ether. By removing the solvent, 41.5 g of compound IIh are obtained.

#### ·· 15 Example 9

10

25

30

35

4-0xiranylmethoxyphenyl 2-hydroxy-2-propyl ketone ([[i]

Analogously to Example 3, 6.8 g of the analytically compound IIi of melting point 54°C are obtained from 20 111.0 g (0.2 mol) of 4-hydroxyphenyl 2-hydroxy-2-propyl ketone and 19.0 g (0.2 mol) of epichlorohydrin.

## Example 10

4-[3-(Triethoxysilyl)propoxy]-phenyl 2-hydroxy-2propyl ketone (IIj)

Analogously to Example 4, 10.2 g of the analytically pure compound II; are obtained from 14.3 g (0.065 mol) of IIg and 16.0 g (0.0975 mol) of triethoxysilane.

# example 11

2-(2-Hydroxyethylthio)thioxanthone (IIIa)

5.6 g (0.0225 mol) of 2-chlorothioxanthone and 2.6 g (0.0225 mol) of the potassium salt of 2-mercaptoethanol are stirred for 18 hours in 20 ml of N,N-dimethylacetamide at 100°C. The reaction mixture is then poured into 2N hydrochloric acid and extracted with ethyl acetate. After contentional work-up and chromatographic purification, 3.5 g of the analytically pure compound IIIa of melting point 94°C are obtained.



# Etimple 12

2-(2-Aminoethylthio)thioxanthone ([[[b]])
17.0 g (0.15 mol) of cysteaminium thloride and
19.3 g (0.3 mol) of potassium hydroxide are boiled for 3
have a water separator in 180 ml of toluene. 24.6 g (0.1
mc.) of 2-chlorothioxanthone and 180 ml of dimethylpropylenesses are added to the evaporated residue, and the mixturn is stirred for 20 hours at 100°C. The reaction mixture
is powed into 1 l of 2N hydrochloric acid and the aqueous
phase is extracted with ethyl acetate. The aqueous phase is

then adjusted to pH 10 and extracted with ethyl acetate. Work-up of the organic phase gives 24.0 g of the analytically oure compound IIIb.

### Erapple 13

10

...: 15

....:

30

? C

35

2-(2-(acryloyloxy)ethylthio]thioxanthone (IIIc)

6.8 g (0.075 mol) of acrylyl chloride in 30 ml of thruene are added dropwise with stirring to 14.0 g (0.05 mol) of compound IIIa, 6.0 g of pyridine and 0.07 g of 4-methoxyphenol in 150 ml of toluene at room temperature. After stirring for 3 hours at 50°C, 500 ml of water and 250 cl of ethyl acetate are added to the mixture. Work-up of the organic phase and chromatographic purification give 5.0 g of the analytically pure compound IIIc of melting point 68-71°C.

## 25 Example 14

2-[2-(Acryloylamino)ethylthio]thioxanthone (IIId)
Analogously to Example 10, 4.6 g of the analytically pure compound IIId of melting point 161°C are obtained from 14.5 g (0.05 mol) of compound IIIb and 5.0 g
(0.055 mol) of acrylyl chloride.

### Example 15

Polymeric photoinitiator

18.6 g (0.05 mol) of 2-[2-(acryloyloxy)ethylthio]-thioxanthone (IIIe) and 0.15 g of dibenzoyl peroxide are refluxed for 20 hours in 100 ml of toluene. The polymeric product obtained is purified by reprecipitation from methylene chloride/n-hexane. A yellow amorphous powder, whose average molecular weight is determined at about 3200

reans of get-permeation chromatography, is obtained.

Examples 16-21 below illustrate the use according to the invention of the coreactive photoinitiators in radic tion curing of photopolymerizable binder systems.

15

25

30

lybrid binder system

weight of a hydroxyl group-containing polyacrylate/about 65% strength in butyl acetate/xylene (Desmophen® A 365, Messrs. Bayer AG), 17.0 parts by weight of an aliphatic polyisocyanate/about 75% strength in methoxypropyl acetate/xylene (Desmodur® N 75, Messrs. Bayer AG), 30.0 parts by weight of an acrylated polyurethane prepolymer (VPS 1748, Messrs. Degussa AG), 20.0 parts by weight of hexanediol diacrylate, 7.5 parts by weight of pentaery-thritol triacrylate and 5.0 parts by weight of the hydroxyl-functionalized photoinitiator IIa was prepared by mixing the components, the polyisocyanate not being acced until just before use.

The ready-to-use hybrid binder system was applied in a coating thickness of 50 µm using a spiral hand coater onto glass plates (10 x 10 cm). After a drying time of 5 minutes, the coatings were cured using a UV irradiator (Messrs. Beltron), through which the plates are fed on a conveyor belt at a belt speed between 2.5 and 40 m/min under two Hg medium-pressure lamps of power 50 watt/cm each at a distance of 10 cm.

At belt speeds between 2.5 and 15 m/min, solid paint chatings with a dry surface were obtained immediately.

Thermal post-curing of the polyurethane reactive rasin component gave a final hardness of the coatings of:

- for 20 hours/room temperature:

168 seconds

- for 1 hour/60°C:

188 seconds

- for 3 hours/60°C:

198 seconds

35 (König pendulum hardness)

After extraction of fully cured coating material with acetonitrile, the proportion of initiator which is not bound into the material is determined by means of high-

pressure liquid chromatography at a maximum of 3% of the criginal amount employed.

In an analogous fashion, equally good results are octained using initiators IIIa and IIIb.

## Example 17

1(

15

∴..;

25

30

35

....

UV-curable binder system

a UV-curable binder system comprising 60 parts by reight if an acrylated polyurethane prepolymer (prepolymer VSP ./48, Messrs. Degussa AG), 40 parts by weight of mexanediol diacrylate, 15 parts by weight of pentaery—thritol triacrylate and 5 parts by weight of the photominitiator IIc which is functionalized with unsaturated groups, was processed analogously to Examples 16 to give 50 µm thick coatings and cured at a belt speed of 10 m/min. The fully cured coatings obtained are entirely free of odon- and colourless.

In an analogous fashion, equally good results are obtained using initiators IIh and IIIc-IIIf.

#### Ex ple 18

UV-curable pigmented binder system

were incorporated homogeneously into 60 parts by weight of an acrylated epoxy prepolymer (Laromer<sup>®</sup> PE 55 F, Messrs.

BASF AG) and 40 parts by weight of hexanedial diacrylate.

4 parts by weight of the thioxanthone photoinitiator IIIc which is functionalized by unsaturated groups and 8 parts by weight of N-methyldiethanolamine as coinitiator are subsequently stirred into the mixture. It was possible to harden the paint, applied to glass plates in a coating thickness of 12 μμ at belt speeds between 2.5 and 20 m/min and an irradiation power of 120 W/cm to rive solid coatings having a dry surface.

At a belt speed of 2.5  $\nu/min$ , the König pendulum hardness is 155 seconds. Paint films are odourless and yellowing-free.

### erascle 19

On curing at 2.5 m/min, the corresponding use of the hydroxyl-functionalized thioxanthone photoinitiator IIIa

- 33 -

gave paint coatings having a pendulum hardness of 149 seconds.

## Example 20

5

10

15

35

TV-curable binder system

with a system comprising 75 parts by weight of an acrylated enaxy prepolymer (Laromer® EA 81, Messrs. BASE AG) and 25 parts by weight of hexanediol diacrylate at a belt speed of 2.5 m/min and an irradiation power of 80 W/cm with initiation using 0.5% by weight of the thioxanthone derivative III2 which is functionalized by unsaturated groups and 2.0% by weight of N-methyldiethanolamine to give paint coatings 12/10g a pendulum hardness of 172 seconds.

## Example 21

Coating curing using substrate-bound initiator A 25% strength ethanolic solution of the silyl-furctionalized photoinitiator IId was whirler coated onto gials plates (5 x 5 cm), and the plates thus treated were heated for 30 minutes at 190°C. The plates were then rinsed with acetone and coated with a mixture of 75 parts by weight of an acrylated epoxy prepolymer (Laromer EA 81, Messrs. BASE AG) and 25 parts by weight of hexanediol diacrylate. After UV curing at 3.75 m/min and an irradiation power of 120 U/cm and rinsing again with acetone, hard, very strongly adherent coatings of thickness 0.7-0.8 µm were obtained. Corresponding results are obtained using initiator

IIi.

The claims defining the invention are as follows:-

Use of compounds of the formula I, **(I)** RG-A-IN

in which

IN is a photoinitiator basic structure



where

R is 
$$-CR^3R^4R^5$$
 or  $-P(R^6)_2$ 

20

25

alternatively -S-, R<sup>2</sup> is H, halogen, C<sub>1-12</sub>-alkyl or C<sub>1-12</sub>-alkoxy or the RG-A- group,

 $R^{1}$  is H,  $C_{1-12}$ -alkyl, halogen or the RG-A- group,

to the carbonyl group together are

or two R<sup>1</sup> radicals in the ortho position

in each case independently of one another are H, C<sub>1-12</sub>-alkyl, C<sub>1-12</sub>-alkenyl, C<sub>1-12</sub>alkoxy or phenyl, or together are C2-6alkylene,

 $R^{5}$  is  $OR^{7}$ ,  $N(R^{7})_{2}$ , -N, -N, N-H, -N or  $SO_{2}R^{7}$ ,

R<sup>6</sup> is C<sub>1-6</sub>-alkyl, C<sub>1-6</sub>-alkanoyl, phenyl or benzoyl, each of which is optionally substituted

by halogen, C1-6-alkyl or C1-6-alkoxy,

 $R^7$  is H,  $C_{1-6}$ -alkyl or  $C_{1-6}$ -alkanoyl, is a spacer group  $Z((CH_Z)_0Y]_n-((CH_Z)_mX]_t$ 

3.)

X, Y and Z, in each case independently of one

unother, are a single bond -0-, -5-, -NH-, -co-, -coo-, -conH-, -0-CO-, -NH-CO- or -NH-COO-,

( and a are the numbers 1 to 4, n and o are the numbers 0 to 4

5

10

. 15

35

is one of the functional reactive groups HO-, HS-, ર હ H<sub>2</sub>N-, halogen, HO-CO-, H<sub>2</sub>N-CO-, O=C=N+, S=C=N-, N<sub>3</sub>-, SO3H, SO2CL; RCRDC=CRa- where Ra, Rb and Rc are in each case H or CH3, and with the proviso that Z is not -COO- when n is O and  $R^5$  is  $OR^7$ ; RG is furthermore halogen, cyclopropyl, oxiranyl, O=C=N-R<sup>d</sup> where R<sup>d</sup> is C<sub>1-6</sub>-alkylene or phenylene,  $N_2^+$  (R<sup>e</sup>)<sub>3</sub>Si where R<sup>e</sup> is halogen, C<sub>1-12</sub>-alkyl, C<sub>1-12</sub>-alkoxy or C<sub>1-12</sub>-alkanoyloxy

as coreactive photoinitiators for photopolymerization of systems containing ethylenically unsaturated compounds.

- Use of the compounds of the general formula I according to Claim 1 together with known photoinitiators and/or sensitizers.
- Use according to Claim 1 in radiation curing of ...: 20 coatings containing UV-curable paint and binder systems.
  - Use according to Claim 1 in radiation curing of hybrid binder systems.
  - Process for photopolymerization of systems containing ethylenically unsaturated compounds, characterized 25 in that at least one compound of the formula I is added as a coreactive photoinitiator to the mixture to be polymerized before initiation of the photopolymerization.
  - Process according to Claim 5, characterized in that 0.1 to 20% by weight of a compound of the formula I are 30 added to the mixture to be polymerized before initiation of he photopolymerization.
    - Photopolymerizable systems containing at least one 7. ethylenically unsaturated, photopolymerizable compound and, if appropriate, further known and conventional additives, tharacterized in that they contain at least one compound of the formula I as a coreactive photoinitiator. Hybrid binder systems, characterized in that they

contain at least one compound of the formula I as a coreactive photoinitiator.

- 9. Photopolymerizable systems according to Claims 7 and 8, characterized in that they contain 0.1 to 20% by weight of a compound of the formula 1.
- 10. Use of compounds of the formula I as synthesis intermediates in the preparation of further-functionalized photoinitiators and of radiation-reactive systems having covalently bound photoinitiators.
- 11. The compounds of the formula I
  4-[2-(oxiranylmethoxy)ethoxy]phenyl 2-hydroxy-2-propyl
  ketone
  - 4-(2-allyloxyethoxy)phenyl 2-hydroxy-2-propyl ketone 4-[2-(3-triethoxysilylpropoxy)ethoxy]phenyl 2-hydroxy-2-
- propyl ketone

  4-(2-azidoethoxy)phenyl 2-hydroxy-2-propyl ketone

  4-(hydroxycarbonylmethoxy)phenyl 2-hydroxy-2-propyl ketone

  4-allyloxyphenyl 2-hydroxy-2-propyl ketone

  4-oxiranylmethoxyphenyl 2-hydroxy-2-propyl ketone
- 20 '-[3-(triethoxysityl)propoxy]phenyl 2-hydroxy-2-propyl ketone
  - 4-[2-(3-triethoxysilylpropylthio)ethyl]phenyl 2-hydroxy-2aropyl ketone
  - 4-(2-chloroethoxy)phenyl (2-hydroxy-2-propyl) ketone
- 25 4-(oxiranylmethoxycarbonylmethoxy)phenyl 2-hydroxy-2-propyl ketone
  - 4-oxiranylmethoxyphenyl a-isopropoxybenzyl ketone
    4-(3-(triethoxysilyl)propoxy]phenyl a-isopropoxybenzyl ketone
- 4-oxiranylmethoxyphenyl α,α-dimethoxybenzyl ketone
  4-(3-(triethoxysilyl)propoxy]phenyl-α,α-dimethoxybenzyl
  ketone
  - 4-(2-isocyanatoethoxy)phenyl 2-hydroxy-2-propyl ketone
  - 4-(2-isothiocyanatoethoxy)phenyl 2-hydroxy-2-propyl ketone
- 35 4-(2-hydroxy-2-methylpropionyl)phenoxyacetamide
  - 4-(2-hydroxy-2-methylpropionyl)phenoxyacetohydrazide
  - N-[4-(2-hydroxy-2-methylpropionyl)phenoxyacetyl]hydroxylamine

N-[4-(2-hydroxy-2-methylpropionyl)phenoxyacetyl]-N'acryloylhydrazine

4-isocyanatomethoxyphenyl 2-hydroxy-2-propyl ketone
vinyl :-(2-hydroxy-2-methylpropionyl) phenoxyacetate

2-(2-hydroxyethylthio) thioxanthone

2-(2-aminoethylthio) thioxanthone

2-[2-(acryloyloxy) ethylthio] thioxanthone

2-[2-(acryloylamino) ethylthio] thioxanthone

2-[2-(allyloxy) ethylthio] thioxanthone

2-[2-(allylamino) ethylthio] thioxanthone

2-[2-(6-isocyanatohexylaminocarbonyloxy) ethoxy] thioxanthone

2-(oxiranylmethoxy) thioxanthone

- 12. A method for photopolymerization of systems containing ethylenically unsaturated compounds, comprising conducting said photopolymerization with coreactive photoinitiators of the formula I shown in claim 1.
- 13. The compounds of formula I as shown in claim 1, said compounds sybstantially as herein described with reference to any one of Examples 1 to 14.
- 14. Binder systems substantially as herein described with reference to any one of Examples 16 to 21.

DATED this 19th day of December, 1990

MERCK PATENT GESELLSCHAFT
MIT BESCHRANKTER HAFTUNG
By Its Patent Attorneys,
ARTHUR S. CAVE 4 CO.



## Abstract of the Disclosure

Compounds of the formula I

RG-A-IN

- (I)

where

IN is a photoinitiator basic structure

A is a spacer group and

RG is a functional reactive group and have the meanings given for these groups in the main claim,

can be employed as coreactive photoinitiators for photopolymerization of systems containing ethylenically unsaturated compounds.

Const of the second state of the second

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

# **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

# IMAGES ARE BEST AVAILABLE COPY.

□ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.